

SETU INDUSTRIES - METODA (INDIA)

SELF PRIMING BARE PUMP

PUMP MODEL	PIPE SIZE	STAGE	R.P.M.	WEIGHT Kg.	MOTOR RATING		DUTY POINT	HEAD & DISCHARGE IN LITERS PER MINUTE					
					KW	H.P.							
SSC-401	40 X 40	1	1440	24.200	1.50	2.00	25	HEAD.M.	15	25	35	45	55
					2.20	3.00	35	L.P.M.	110	95	80	60	45
SSC-402	40 X 40	2	1440	29.300	2.20	3.00	45	HEAD.M.	25	45	65	75	95
					3.70	5.00	65	L.P.M.	105	90	70	60	40
SSC-403	40 X 40	3	1440	36.200	5.50	7.50	60	HEAD.M.	40	60	80	100	130
					7.50	10.00	80	L.P.M.	125	115	105	90	75
SSC-404	40 X 40	4	1440	41.300	7.50	10.00	80	HEAD.M.	60	80	100	130	150
					9.30	12.50	130	L.P.M.	130	120	115	100	90

>>>>>> Applications

- * Domestic & Agricultural use
- * Water circulation & Boiler feeding
- * Chemical pumping & Circulation for industrial coolers
- * High head usage & Pumping in estates

SETU INDUSTRIES - METODA (INDIA)

SELF PRIMING BARE PUMP

PUMP MODEL	PIPE SIZE	STAGE	R.P.M.	WEIGHT Kg.	MOTOR RATING		DUTY POINT	HEAD & DISCHARGE IN LITERS PER MINUTE					
					KW	H.P.		HEAD.M.		L.P.M.			
SSC-251	25 X 25	1	1440	17.000	0.75	1.00	15	10	15	25	35	40	
					1.10	1.50	25	65	55	40	30	20	
SSC-252	25 X 25	2	1440	20.500	1.10	1.50	25	15	25	30	40	50	
					1.50	2.00	40	65	55	45	35	25	
SSC-253	25 X 25	3	1440	24.000	2.20	3.00	40	20	40	60	80	100	
					3.70	5.00	80	65	50	40	25	10	
SSC-254	25 X 25	4	1440	28.000	3.70	5.00	60	40	60	80	100	135	
					5.50	7.50	100	55	45	35	25	10	

>>>>>> Applications

- * Domestic & Agricultural use
- * Water circulation & Boiler feeding
- * Chemical pumping & Circulation for industrial coolers
- * High head usage & Pumping in estates

SETU INDUSTRIES - METODA (INDIA)

SELF PRIMING BARE PUMP

PUMP MODEL	PIPE SIZE	STAGE	R.P.M.	WEIGHT Kg.	MOTOR RATING		DUTY POINT	HEAD & DISCHARGE IN LITERS PER MINUTE					
					KW	H.P.							
SSC-501	50 X 50	1	1440	40.000	2.20	3.00	15	HEAD.M.	10	15	20	25	35
					3.70	5.00	35	L.P.M.	300	270	250	200	150
SSC-502	50 X 50	2	1440	49.000	5.50	7.50	40	HEAD.M.	10	20	40	50	65
					7.50	10.00	50	L.P.M.	325	290	220	180	110
SSC-503	50 X 50	3	1440	58.300	9.30	12.50	60	HEAD.M.	20	60	80	95	105
					11.00	15.00	105	L.P.M.	340	260	220	190	160
SSC-504	50 X 50	4	1440	67.500	15.00	20.00	110	HEAD.M.	30	60	90	110	140
					18.70	25.00	140	L.P.M.	330	260	210	160	70

>>>>>> Applications

- * Domestic & Agricultural use
- * Water circulation & Boiler feeding
- * Chemical pumping & Circulation for industrial coolers
- * High head usage & Pumping in estates